





8 7 6 5 4 3 2 1



NOTES:

- 1) MATERIAL: 17-4 PH STAINLESS STEEL, H900 OR H925 CONDITION
MIN UTS = 170 KSI (38 HRc)
(REF DART SPEC. D6104)
- 2) FINISH: NONE
- 3) TOLERANCES: PER DART QSI 018 (REF X.XXX = ±0.010) UNLESS OTHERWISE NOTED
- 4) UNITS: INCHES UNLESS OTHERWISE NOTED
- 5) BREAK SHARP EDGES: 0.005 TO 0.010 MAX
- 6) IDENTIFICATION: DART LOGO (PER DART SUPPLIED GRAPHIC) AND PART NUMBER IN THIS AREA WITH 0.125 HIGH LETTERING
0.010-0.020 DEEP, PER DART QSI 044 6.3.
- 7) WEIGHT: 0.78 lb
- 8) FOR THE ENTIRE INNER CONCAVE SURFACE:
ABRADE SURFACE WITH 400-GRIT SANDPAPER. REMOVE RESIDUE WITH MEK (OR EQUIVALENT). APPLY 0.03" TO 0.05" THICK LAYER OF 3M SCOTCH-WELD 2216 B/A ADHESIVE TO MATING SURFACE OF SUPPORT. ALLOW TO CURE FOR 24 HOURS.

D2893-1 SUPPORT

C	RMV FINISH, ADD 3M 2216, ADD H925 MAT'L OPTION	CP	11.07.15
B	UPDATE DIMS AS MFG, PRIME INSIDE	PH	07.03.16
A	NEW ISSUE	CP	01.01.10
REV.	DESCRIPTION	BY	DATE
DESIGN	q	DART AEROSPACE LTD HAWKESBURY, ONTARIO, CANADA	
DRAWN	q		
CHECKED	ASS	DRAWING NO.	REV. C
MFG. APPR.		D2893	SHEET 1 OF 1
APPROVED		TITLE	SCALE
DE APPR.		Ø2.750 SUPPORT	NTS
DATE	11.07.15	COPYRIGHT © 2001 BY DART AEROSPACE LTD THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS NOT TO BE USED FOR ANY PURPOSE OR COPIED OR COMMUNICATED TO ANY OTHER PERSON WITHOUT WRITTEN PERMISSION FROM DART AEROSPACE LTD.	

RELEASED
2011-07-28